
















<u>Type</u>	<u>Complet</u>	<u>Tête</u>	<u>Tige A</u>	<u>Tige B</u>	<u>Tige C</u>
					
R 8-3	X				
R 8-5	X				
R 8-7	X				
R 8-8	X				
R 8-P3 (cône)	X (modifié)				
R 8 à compensation	X				
R 10-3	X				
R 10-5	X				
R 10-6	X				
R 10-7	X				
R 10-8	X				
R 10-10 (taraud.)	X (modifié)				
R 10 à compensation	X				
R 12-3	X				
R 12-5	X				
R 12-7	X				
R 12-8	X				
R 12-1/4	X				
R 12 à compensation	X				
R 14-3	X				
R 14-5	X				
R 14-7	X				
R 14-8	X				
R 14 à compensation	X				
R 16-3	X				
R 16-4	X				
R 16-5	X				
R 16-6	X				
R 16-6 SP lubrif.	X (modifié)				
R 16-7	X				
R 16-8	X				
R 16 à compensation	X				

<u>Type</u>	<u>Complet</u>	<u>Tête</u>	<u>Tige A</u>	<u>Tige B</u>	<u>Tige C</u>
					
R 19-5	X				
R 19-8	X				
R 19 à compensation	X				
R 25-5	X				
R 25-6	X				
R 25-7	X				
R 25-8		X			X
R 25-10		X	X		
R 25-14		X		X	
R 25 à compensation	X				
R 25 Nomura		X (+ tige sp.)			
R 27-6	X				
R 27-7	X				
R 27-8		X			X
R 27-8 C		X			X
R 27-10		X	X		
R 27-12		X		X	
R 27-14		X		X	
R 27-21 (taraud.)		X (+ tige sp.)			
R 27 à compensation		X (+ 0775000.)			
R 32-6 SP lubrif.		X			X (spéciale)
R 32-8		X			X
R 32-10		X			X
R 32-12		X	X		
R 32-14		X		X	
R 32-16		X		X	
R 32-21 (taraud.)		X (+ tige sp.)			
R 32 à compensation		X (+ 0775000.)			
R 35-10		X			X
R 35-12		X	X		
R 35-14		X		X	
R 35-14 L		X		X	
R 35 à compensation		X (+ 0775000.)			

Type	Complet	Tête	Tige A	Tige B	Tige C
					
R 40-12		X	X		
R 40-14		X		X	
R 40-14 L		X		X	
R 40-16		X		X	
R 40-16 SP		X (+ tige sp.)			
R 40-20		X		X	
R 40 à compensation		X (+ 0775000.)			

Type PF	Ø Clearance (std)	Max. thread length	Max. drill diameter
N 6	3.20	12.00	1.50
N 6 P 3	3.20	9.50	(Broche Petermann)
N 8	3.20	13.00	1.50
N 8 P3	3.20	10.50	(Broche Petermann)
N 12	4.20	16.50	2.00
N 12 P3	4.20	14.00	(Broche Petermann)
N 12 P4	5.00	14.00	(Broche Petermann)
F 8-5	5.20	28.50	3.00
F 8-6	5.20	11.50	4.00
F 8-7	5.20	28.50	5.20
F 8-8 L50	5.20	28.50	5.20
F 8-8 C L25	5.20	28.50	5.20
F 8-8 T L100	5.20	28.50	5.20
F 8-10	5.20	28.50	5.20
F 10-8 C L20	7.20	12.00	6.00
F 10-9 L60	7.20	12.00	6.50
F 10-10 L21	7.20	12.00	6.50
F 11-8	8.20	11.00	8.20
F 12-7	9.40	11.00	9.40
V 10-8	6.50	25.00	6.00
V 10-10	6.50	25.00	6.50
V 10-10 SP (R10)	6.50	37.00	6.00
V 10-10 C	6.50	25.00	6.50
V 10-12	6.50	25.00	6.50
V 10-14	6.50	25.00	6.50
V 12-14	8.60	24.00	8.60
V 15-9	12.60	23.00	7.00
R 8-3	3.80	16.00	1.50
R 8-5	3.80	16.00	2.50
R 8-7	3.80	16.00	3.80
R 8-8	3.80	16.00	3.80
R 10-3	4.00	17.00	1.50
R 10-5	4.00	17.00	2.50
R 10-6	4.00	17.00	3.50
R 10-7	4.00	17.00	4.00
R 10-8	4.00	17.00	4.00
R 12-3	5.40	17.00	1.50
R 12-5	5.40	17.00	2.50
R 12-7	5.40	17.00	4.00
R 12-8	5.40	17.00	5.40
R 12-1/4	5.40	17.00	5.40
R 14-3	6.50	18.00	1.50
R 14-5	6.50	18.00	2.50
R 14-7	6.50	18.00	4.00
R 14-8	6.50	18.00	5.50
R 16-3	7.40	19.00	1.50
R 16-4	7.40	19.00	2.00
R 16-5	7.40	19.00	2.50
R 16-6	7.40	19.00	3.50
R 16-7	7.40	19.00	4.00
R 16-8	7.40	19.00	5.50

